



**The Unofficial Totally Made Up OpticanWorks Standards
For Practice Use Only**

Standard For	When Power Is	Then Tolerance Is
Sphere Power Single Vision and Lined Multifocals	0.00 to 6.50 Greater than 6.50	0.13 D 2%
Cylinder Power Single Vision and Lined Multifocals	0.00 to 2.00 Greater than 2.00 to 4.50 Greater than 4.50	0.13 D 0.15 D 4%
Sphere Power Progressives (PALS)	0.00 to 8.00 Greater than 8.00	0.16 D 2%
Cylinder Power Progressives (PALS)	0.00 to 2.00 Greater than 2.00 to 3.50 Greater than 3.50	0.16 D 0.18 D 5%
Cylinder Axis <i>Using cylinder power</i>	0.12 to 0.25 Greater than 0.25 to 0.50 Greater than 0.50 to 0.75 Greater than 0.75 to 1.50 Greater than 1.50	14° 7° 5° 3° 2°
PD Horizontal Prism	0.00 to 2.75 Greater than 2.75	0.67 D 2.5mm
OC Vertical Prism	0.00 to 3.37 Greater than 3.37	0.33 D 1.0mm
Add Power	Less than or equal to +4.00 Greater than +4.00	0.12 D 0.18 D
PD Horizontal Prism (PALS)	0.00 to 3.37 Greater than 3.37	0.67 D 1.0mm
OC Vertical Prism (PALS)	0.00 to 3.37 Greater than 3.37	0.33 D 1.0mm
Segment Height		+/- 1.00mm

FOR PRACTICE USE ONLY!